



## PRODUCT SPECIFICATION & TECHNICAL DATA

### **PW48 - PW Classic Plus Ear Muff**

**Collection:** Ear Muffs

**Range:** Hearing Protection

**Materials:** ABS, Polyoxymethylene, PVC

---

### **Product information**

Lightweight and flexible the Classic Plus is adjustable and extremely comfortable to wear. Suited to long term use.

---

### **Standards**

EN 352-1 (SNR 28dB)

### **Ear Muffs**

Portwest Hearing protection range includes PPE with different level sound attenuation, to be adapted to various working environments giving the correct protection from dangerous noise, without isolating the workers. New models and colours for earmuffs allow a personalised choice. An updated range of earplugs complete our competitive and performing offer.

### **Hearing Protection**

Hearing problems occur when you are exposed to hazardous working conditions without wearing the correct protective equipment.

---

### **Features**

- Ultra lightweight for long uses
- Padded headband for comfort
- Adjustable length for a secure and comfortable fit
- 100% metal free
- CE certified
- CE-CAT III
- Retail bag which aids presentation for retail sales
- Individually packed for vending machines





## PRODUCT SPECIFICATION & TECHNICAL DATA

### PW48 - PW Classic Plus Ear Muff

Commodity Code: 6506101000

#### Test House

BSI Group The Netherlands B.V. (Notified Body No.: 2797)

Say Building, John M. Keynesplein 9, 1066 EP

, Netherlands

Cert No: CE 698123

#### Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m <sup>3</sup> )	EAN13	DUN14
PW48YER	Yellow	48.0	40.0	60.0	0.1780	0.1152	5036108258987	15036108748218

## PERFORMANCES - SOUND ATTENUATION - EN 352-1:2002

<b>PW48</b>		<b>SNR 27.6dB</b>				<b>H: 30.4 M: 24.9 L: 17.7</b>			
A	Frequency (Hz)	<b>63</b>	<b>125</b>	<b>250</b>	<b>500</b>	<b>1000</b>	<b>2000</b>	<b>4000</b>	<b>8000</b>
B	Mean Attenuation (dB)	19.0	16.0	18.3	25.9	30.6	31.7	34.5	38.1
C	Standard Deviation (dB)	5.7	5.0	2.5	2.8	1.6	3.4	2.8	2.6
D	Assumed Protection (dB)	13.3	11.0	15.8	23.1	28.9	28.3	31.7	35.5

PW48YER